

## FISA TEHNICA – BANDA ADEZIVA DIN ALUMINU NETED

ALUMINIU	tip 1200, monolucid
ADEZIV	sintetic
LINER	hartie siliconata
GROSIME	30, 40 sau 50µm      EN 546/3

In tabelul urmatore sunt cuprinse valorile nominale, valorile minime si maxime de toleranta

Grosime	30 microni	40 microni	50 microni
Minim	28.8	38.4	48.0
Maxim	31.2	41.6	52.0

TEMPERATURA DE APLICARE	intre +10°C si +35°C	
TEMP DE LUCRU ADEZIV	intre -20°C si +75°C	
REZISTENTA LA FOC	clasa 1 (referitor la material)	B.S. 476 PART 7
ALUNGIREA	3-5% (30µ ), 5-7% (40µ ), 7-10% (50µ )	ASTM E 345
REZISTENTA LA RUPERE	1,2 N/cm	ASTM E 345
ADERENTA PE OTEL (Peel)	400 N/cm	PSTC n.1
ADERENTA PROPRIE	450 N/cm	PSTC n.1
DIMENSIUNE CUTIE	260 x 260 x 300mm	
NR. CUTII PE PALET	48	

COD PRODUS	GROSIME	LATIME	LUNGIME	BUC/CUTIE
HMH50L30-50	30µ	50mm	50m	24
HMH75L30-50	30µ	75mm	50m	16
HMH100L30-50	30µ	100mm	50m	12
HMH50L40-50	40µ	50mm	50m	24
HMH75L40-50	40µ	75mm	50m	16
HMH100L40-50	40µ	100mm	50m	12
HMH50L50-50	50µ	50mm	50m	24
HMH75L50-50	50µ	75mm	50m	16
HMH100L50-50	50µ	100mm	50m	12